



ORDERING INFORMATION

SERIES NO. J0201  
 TYPE C  
 PRODUCTS HIGH 3  
 PIN NO. XX  
 CONTACT PLATING ME PLATING ATTACHMENT XX  
 PACKING TYPE MYLAR OR CAP X  
 N/W/O MYLAR OR CAP  
 2:WITH MYLAR 6.6X4.0  
 3:WITH MYLAR 1.38X4.0  
 4:WITH MYLAR W:WITH CAP (2.40H&3.80H&4.40H&4.90H)  
 12 20:MATTE-TIN 30:BRIGHT-TIN  
 30:BRIGHT-TIN 1:WITH PEG  
 61:GOLD FLASH 1/4"  
 63:GOLD FLASH 4/4"  
 65:GOLD FLASH 10/4"  
 21:TAP&REEL (24mmB2 WITH LEFT PEG)  
 22:TAP&REEL(32mmB2)

MATERIAL  
 INSULATOR: GLASS FILLED THERMO-PLASTIC. UL 94V-0  
 CONTACT: JIS C5191 R-H  
 THIS PART DONT CONTAIN ANY SUBSTANCES WHICH ARE SPECIFIED IN SS-00259

SPECIFICATION  
 CURRENT RATING: 0.5A 50V AC/DC  
 CONTACT RESISTANCE: 40mΩ MAX  
 INSULATION RESISTANCE: 500MΩ MIN AT 500V DC  
 OPERATING TEMPERATURE RANGE: -20°C TO +85°C

DIM	A	B	C	D	E	F
PIN	12	4.0	5.0	5.6	9.0	6.25
30	11.2	12.2	12.8	16.2	13.45	15.2

PRODUCT ASSEMBLY HIGH	PART NO.	CAP PART NO.
H=3.0mm	J0201-P1	J0201-C1
H=3.5mm	J0201-P1	J0201-C4
H=4.4mm	J0201-P1	J0201-C3
H=5.0mm	J0201-P1	J0201-C2
H=5.5mm	J0201-P1	J0201-C5
H=7.0mm	J0201-P1	J0201-C6
H=11.0mm	J0201-PF	J0201-CE
H=15.0mm	J0201-PF	J0201-CE

INTENDED USE	TITLE	PART NO.	CHKD	DATE
CUSTOMER	CAP ASSEMBLY (MATING HEIGHT 3.80mm WITH BOSS) 0.8mm PITCH BTB CONN.	J0201-C3XXXXXX1XXX	Steve	08/06/09'
TOLERANCES		J0201-C3XXXXXX1XXX	Mark	
	LINEAR 0.0 ±0.30			
	ANGLES ±3°			

JJP Jen Jia Precision Co., LTD.

SCALE	SHEET	REV	UNIN
1:1	1/1	A	mm