



Specification

***Electrical Characteristics:**

Contact Current Rating:0.5Amperes.
 Dielectric Withstanding Voltage:AC 500V r.m.s.
 Insulation Resistance:100 Megohms Minimum
 Contact Resistance:40 Miniloohms Maximum.

***Mechanical Characteristics:**

Contact Retention Force:100g Min.

***Environmental:**

Operating TemperatureL:-25°C~+85°C.

***Materials:**

Insulator:Hi-Temp Plastic UL 94V-0.
 Contact:Copper Alloy(T=0.20mm).
 Pad:Copper Alloy(T=0.20mm).

J02016-5231-1

1:有耳
 2:無耳

P.C.B. LAYOUT
 TOP VIEW

INTENDED USE		TITLE		JJP Jen Jia Precision Co., LTD.		Board TD Board 排針	
CUSTOMER		PART NO.		J02016-5231		APPRD Mark	
TOLERANCES		DRAW NO.		J02016-5231		CHKD Steve	
0~6±0.1 X:±1.5'		MATERIAL		SEE NOTE		DRAW Tina	
6~20±0.2 X'±1'		FINISH		SEE NOTE		DATE CH 2006/10/5	
20~90±0.3.XX'±0.5'		SCALE		SHEET 1/1		REV A	
						UNIN mm	

