



PCB LAYOUT
TOP VIEW

Specification

*Electrical Characteristics:

Contact Current Rating:0.5Amperes.
Dielectric Withstanding Voltage:AC 500V r.m.s.
Insulation Resistance:100 Megohms Minimum
Contact Resistance:40 Milliohms Maximum.

*Mechanical Characteristics:

Contact Retention Force:100g Min

*Environmental:

Operating TemperatureL:-25°C~+85°C.

*Materials:

Insulator:Hi-Temp Plastic UL 94V-0.

Contact:Copper Alloy(T=0.20mm).

Pad:Copper Alloy(T=0.20mm).

J02016-5241-1

1:有耳
2:無耳

INTENDED USE	CUSTOMER
TOLERANCES	
0~6±0.1 X:±1.5°	
6~20±0.2 X:±1°	
20~90±0.3.XX:±0.5°	

JJP Jen Jia Precision Co., LTD.

TITLE	Board T□ Board 排針
PART NO.	J02016-5241
APPRD	Mark
CHKD	Steve
DRAW	Tina
DATE	CH 2006/10/15

SCALE	1/1	SHEET	1/1	REV	A	UNIN	mm
FINISH	SEE NOTE	DATE	CH	2006/10/15			

INTENDED USE	CUSTOMER
TOLERANCES	
0~6±0.1 X:±1.5°	
6~20±0.2 X:±1°	
20~90±0.3.XX:±0.5°	