


6	4# CONTACT FOOT	1	BRASS	Ag-Plating
5	HOUSING	1	PA66	
4	AXIS SUPPORT	1	BRASS	Ni-Plating
3	3# CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
2	2# CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
1	1# CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
	NO. DESCRIPTION		QTY	MATERIAL
				PLATING

- SPECIFICATION**
1. Rating DC 30V 0.5A
 2. Contact resistance $\leq 30\text{m}\Omega$
 3. Insulation resistance 100Mohms (DC250V)
 4. Withstand voltage 500VAC
 5. Insertion and extraction force 3-30N
 6. Life test 5,000 cycles



INTENDED USE		TITLE		2.5 mm PHONE JACK	
CUSTOMER		PART NO.		J161025-0265	
TOLERANCES		DRAW NO.		J161025-0265	
0~6±0.1 X:±1.5°		MATERIAL		SEE NOTE	
6~20±0.2 X:±1°		FINISH		SEE NOTE	
20~90±0.3 XX:±0.5		SCALE		1/1	
		DATE		CH 2008/02/22	
		REV		A	
		UNITS		mm	

JJP Jen Jia Precision Co., LTD.

1 2 3 4 5 6 7 8

A B C D E