



PCB LAYOUT TOLERANCE:±0.05
BOTTOM VIEW

NOTE:
MATERIAL:

- 1). TERMINAL: PHOSPHOR BRONZE
- 2). TERMINAL PLATED: GOLD FLASH ON CONTACT AREA AND PLATING Au ON DIP DEPARTMENT OVER 50~100u" MIN. NICKEL.
- 3). FRONT SHELL: BRASS T=0.30mm
BACK SHELL: SPCC. T=0.30mm
SPRING SHELL: BRASS T=0.30mm
- 4). FRONT SHELL SPRING SHELL PLATED: TIN PLATED
BACK SHELL : NICKEL PLATED
- 5). HOUSING: P.B.T+30% G.F(UL94V-0) RATED

SPECIFICATION

- 1). CONTACT RESISTANCE: 30mΩ (MAX)
- 2). INSULATION RESISTANCE: 1000MΩ (MIN)
- 3). DIELECTRIC: WITHSTANDING VOLTAGE: 750V AC AT SEA LEVEL
- 4). MATING FORCE: 35N MAX
UNMATING FORCE: 10N MIN.

JJP Jen Jia Precision Co., LTD.

INTENDED USE	TITLE		USB	
CUSTOMER	PART NO.	J2119-2103	APPRD	Mark
TOLERANCES	DRAW NO.	J2119-2103	CHKD	Steve
0~6±0.1 X:±1.5'	MATERIAL	SEE NOTE	DRAW	Tina
6~20±0.2 X:±1'	FINISH	SEE NOTE	DATE	CH 2006/10/5
20~90±0.3.XX±0.5	SCALE	SHEET	REV	UNIN
	1/1	1/1	A	mm