



LOCK SCREW

DIM	A $\pm 0.20$	B $\pm 0.20$	C $\pm 0.20$	D $\pm 0.10$	E $\pm 0.20$	F $\pm 0.20$
PIN						
009	30.80	25.00	16.92	8.30	12.55	5.90
015	39.20	33.32	25.25	8.30	12.55	5.90
019	44.80	38.86	30.60	8.30	12.55	5.90
023	50.30	44.30	36.10	8.30	12.55	5.90
025	53.05	47.04	41.00	8.30	12.55	5.90
037	69.40	63.50	57.60	8.30	12.55	5.90

- NOTES:
- MATERIAL:  
INSULATOR: PBT +30%GF (BLUE)  
CONTACTS: BRONZE  
SHELL: SPCC  
LEISTER: IRON
  - FINISH:  
CONTACTS: NICKEL PLATING BOTTOM/50U"  
PLATING TINI00U" FUNCTION AREA PLATING1U"  
SHELL: SURFACE PLATING NI100U"  
LEISTER: PLATING BOTTOM NI 50U", PLATING S180-120U"
  - PART NUMBER: J419212-1311-XXX 3 3

PIN NO SEE TAB 3. TRAY  
3. SELECTIVE GOLD FLASH

**JJP Jen Jia Precision Co., LTD.**

INTENDED USE: D-SUB MALE PCB TYPE WITH HEX SCREW  
CUSTOMER: J419212-1311-XXXX33 APPROD Mark Steve

TOLERANCES: DRAW NO. J419212-1311-XXXX33 CHKD DRAW TINA

ANGLE: X $\pm$  0.30 X $\pm$  2°  
FINISH: SEE NOTE DATE 4-21-08  
SCALE: 1/1 SHEET 1/1 UNIN mm

