



NOTES:
 1. MATERIAL:
 INSULATOR: PBT +30%GF (BLUE)
 CONTACTS: BRONZE
 SHELL: SPCC
 LEISTER: IRON

2. FINISH:
 CONTACTS: NICKEL PLATING BOTTOM&OU"
 PLATING TIN100" FUNCTION AREA PLATING1U"
 SHELL: SURFACE PLATING NI100"
 LEISTER: PLATING BOTTOM NI 50U", PLATING SI80-120U"

3. PART NUMBER: J419212-1313-XXX 3 3
 PIN NO SEE TAB 3. SELECTIVE GOLD FLASH
 3. TRAY

PIN DIM	A	B	C	D	E
009	30.81	24.99	16.92	19.28	10.72
015	39.14	33.32	25.25	27.65	10.72
025	53.04	47.04	38.96	41.30	10.72
037	69.32	63.50	55.42	57.44	10.72

INTENDED USE	D-SUB MALE SOLDER BUCKET			
CUSTOMER	WITH TURNED CONTACTS			
TOLERANCES	PART NO.	J419212-1313-XXX33	APPRD	Mark
X± ---	DRAW NO.	J419212-1313-XXX33	CHKD	Steve
X.X± 0.30	MATERIAL	SEE NOTE	DRAW	Tin0
X.XX± 0.25	FINISH	SEE NOTE	DATE	4-21-08
X.XXX± 0.20	SCALE	1:1	REV	A
	SHEET	1/1	UNIN	mm

JJP Jen Jia Precision Co., LTD.

1 2 3 4 5 6 7 8

1 2 3 4 5 6 7 8