



RECOMMENDED FOOTPRINT PATTERN

- NOTES:
1. MATERIAL:
HOUSING : HIGH TEMPERATURE THERMOPLASTIC UL94V-0
HOUSING COLOR: NATURAL
CONTACT : COPPER ALLOY
GROUND CONTACT : COPPER ALLOY
 2. PLATING:
CENTER CONTACT: Au 4u" MIN. OVER Ni 50u" MIN. ON CONTACT AREA
GROUND CONTACT: Au OR Ag OVER Ni ON CONTACT AREA(SEE PLATING TABLE)
 3. GENERAL TOLERANCE : ±0.1
 4. PLATING TABLE

Sect. A-A S=12/1

PART NUMBER	GROUND CONTACT PLATING	PACKING
JAM-1000-000-3	GOLD FLASH OVER Ni 50u" MIN.	TAPE & REEL (5000PCS/13" REEL)
JAM-1000-000-4	GOLD FLASH OVER Ni 50u" MIN.	TAPE & REEL (2500PCS/10" REEL)
JAM-1010-000-3	Ag 100u" MIN. OVER Ni 10u" MIN.	TAPE & REEL (5000PCS/13" REEL)
JAM-1010-000-4	Ag 100u" MIN. OVER Ni 10u" MIN.	TAPE & REEL (2500PCS/10" REEL)

INTENDED USE	QTY	FINISH	FILE NO.	TITLE
CUSTOMER				Micro Coaxial Connector Receptacle Vertical Type
PART NO. JAM-1000-000-3		MATL	APPR. POU CHKD. THO	DWG NO.: JAM-1000-000-3
TOLERANCES 0-6±0.1 X:±1.5 6-20±0.2 X:±1 20-90±0.3 XX:±0.5			DR: TW 2007/11/07	SCALE : 1:1
				SHEET: 1/1

JJP Jen Jia
Precision Co., LTD.